

**Pyrok Acoustement Plaster 20**  
**Material Safety Data Sheet**

Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.		U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072		
Identity (As Used on Label and List) <b>Pyrok Acoustement Plaster 20</b>		<i>Note:</i> Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.		
<b>SECTION I</b>				
Manufacturer's Name <b>Pyrok, Inc.</b>		Emergency Telephone Number <b>914-777-7070</b>		
Address (Number, Street, City, State and Zip Code) <b>24 Barry Drive NE</b> <b>White, GA 30184</b>		Telephone Number for Information <b>770-427-9765</b> Date Prepared <b>Revised 01/01/2015</b> /Signature of Preparer ( <i>optional</i> )		
<b>SECTION II – Hazardous Ingredients/ Identity Information</b>				
Hazardous Components (Specific Chemical Identity: Common Name (s)    OSHA PEL    ACGIH TLV    Other Limit    % (optional) Recommended				
<b>Gypsum Plaster CAS #7778-18-9</b>		<b>5-15mg/M<sup>3</sup></b>	<b>10mg/M<sup>3</sup></b>	
<b>SECTION III – Physical/Chemical Characteristics</b>				
Boiling Point	<b>N/A</b>	Specific Gravity (H <sub>2</sub> O=1)		
Vapor Pressure (mm Hg)	<b>N/A</b>	Melting Point		
Vapor Density (AIR=1)	<b>N/A</b>	Evaporation Rate (Butyl Acetate = 1)		
Solubility in Water <b>Yes</b>		Wet Density Avg.		<b>69.5 pcf</b>
Appearance and Odor <b>Grey, slurry and odorless</b>				
<b>SECTION IV – Fire and Explosion Hazard Data</b>				
Flash Point (Method Used) <b>None</b>	Flammable Limits <b>None</b>	LEL	UEL	
EXTINGUISHING MEDIA <b>N/A</b>				
Special Fire Fighting Procedures <b>Totally incombustible, approved for fire protection by UNDERWRITERS LABORATORIES</b>				
Unusual Fire and Explosion Hazards <b>None</b>				

<b>SECTION V – Reactivity Data</b>			
Stability	Unstable		Conditions to Avoid
	Stable	<b>Yes</b>	
Incompatibility (Materials to Avoid)			
Hazardous Decomposition or Byproducts			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	<b>X</b>	
<b>SECTION VI – Health Hazard Data</b>			
Route (s) of Entry:	Inhalation?	Skin?	Ingestion?
Health Hazards (Acute and Chronic) <b>None</b>			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
Signs and Symptoms of Exposure <b>None</b>			
Medical Conditions Generally Aggravated by Exposure			
Emergency and First Aid Procedures <b>Rinse with clean water</b>			
<b>SECTION VII – Precautions for Safe Handling and Use</b>			
Steps to Be Taken in Case Material is Released or Spilled <b>No special steps required. Clean with clean water.</b>			
Waste Disposal Method <b>Treat like all cementations waste disposal methods</b>			
Precautions to Be Taken in Handling and Storing <b>Dust masks should be worn when handling this product and other products generating air born dust.</b>			
Other Precautions			
<b>SECTION VIII – Control Measures</b>			
Respiratory Protection ( <i>Specify Type</i> ) <b>Normal dust masks</b>			
Ventilation			
Protective Gloves	Local Exhaust	Special	<b>None</b>
	Mechanical (General)	Other	<b>Moving air</b>
Protective Gloves <b>Optional</b>	Eye Protection <b>Optional</b>		
Work/Hygienic Practices <b>None</b>			
Work/Hygienic Practices			